

S AND S CHEMICAL COMPANY INC.

S&S Chemical manufactures, warehouses and distributes metalworking/lubrication additives, rust and corrosion inhibitors, emulsifiers and other specialty chemicals.





ABOUT (S

The Gold Standard In Chemistry

S&S Chemical is a 65-year-old wholesale raw material distributor with a sales office in New York. Our company sells to Fortune 500 companies and small businesses in lubrication, machining, automotive, cosmetics and various industrial applications. Our Company provides sales support, customer service and warehouses for products across the United States. What can we make for you?

The History of S&S Chemical has its roots in a separate import-export company located in downtown New York. Back in the 1920's the company imported everything from natural sponges, cork and natural oils well before the synthetic versions were invented. By the 1940's one of the chemists hit upon the idea of sulfurized fats that became a big product line along with the idea of developing specialty products for the customers' needs.

In the 1950's, a need for more efficient distribution brought together Jim Smith and Ed Schumacher to start S&S Chemical Company. S&S handled these sulfurized fats along with waxes from Ed's business. In the 60's the company expanded into handling Chevron and Cosden Polybutenes. Distribution was in its infancy still, as products such as sulfurized fats sold for 8c per pound and tall oil was less than 20c per pound.

Most distribution was regional in those days, but by the 1990's S&S started following the customer base to other parts of the country and opening other warehouses so we could more efficiently stock for our customers. Today we partner with many customers and suppliers to be an extension of their inventories.



TABLE OF CONTENTS

- EP Additives
- Corrosion Inhibitors
- Esters
- Biocides
- Conditioners
- Specialty Amines
- Emulsifiers
- Defoamers
- Antioxidants
- Oleotall/Diacid
- Miscellaneous



EP SULFUR ADDITIVES

S&S LC-40

S&S LC-40 is a 40% active sulfurized olefin. It is low in odor and light in color, suitable for use in neat oils and semi-synthetics.

S&S 20

S&S 20 is a 20% inactive sulfurized olefin.

S&S 42

S&S 42 is a 40% inactive sulfurized olefin. Designed to be light in color, have mild odor and high sulfur content.

S&S LC-2515

S&S LC-2515 is an inactive sulfurized vegetable fatty acid with outstanding EP properties suitable for greases, slideway oils & metal forming.

S&S LC-30

S&S LC-30 is a unique 30% inactive sulfurized olefin. It is low in odor and light in color, less corrosive on yellow metals.

S&S LC-22HP

Is an inactive sulfurized olefin. Designed to be light in color, have mild odor, high sulfur content and high flash point.

S&S PES D & PES L - New Product

S&S PES-D and S&S PES-L are sulfur-phosphorous EP agents that have excellent EP and good anti-wear performance from low treat level. Such an excellent EP performance is suitable for the metal working of hard-to-work materials and contributes to extended tool life.



EP PHOSPHATE ADDITIVES

S&S 497-P

S&S 497-P is a phosphate ester of ethoxylated alcohol. Excellent EP and boundary lubrication properties for machining steel, aluminum, and other metals.

S&S LB-400

S&S LB-400 may be used in metalworking formulations for improved lubricity, wetting, detergency, co-emulsification and corrosion inhibition.

S&S LP-700

S&S LP-700 may be used in metalworking formulations for improved lubricity, wetting, detergency, co-emulsification and corrosion inhibition.

S&S NF-3

S&S NF-3 is an oil soluble corrosion inhibitor for aluminum in soluble, semi-synthetic and synthetic oils.

PEL-PHOS 885-A

PEL-PHOS 885-A is a water soluble, phosphorus containing EP agent, provided in free acid form which enhances lubricity.

Ask us about our unique phosphate esters with coemulsification and hydrotroping properties

EP CHLORINE ADDITIVES

S&S 152

S&S 152 is a 52% mid-chain chlorinated paraffin that is a non-flammable, non-corrosive, low volatile liquid at room temperature that is typically applied in machining, drawing and stamping fluids.

S&S 156

S&S 156 is a 56% mid-chain chlorinated compound used in a wide variety of applications including flame retardants, plasticizers and for EP.



ESTERS

S&S C-1550

S&S C-1550 is a unique fatty acid ester, designed as an extreme pressure lubricity additive in; straight oil, soluble oil, semi-synthetic and synthetic metal removal fluids, rolling oils, and drawing and stamping fluids.

S&S BN-6000

S&S BN-6000 is a polymerized, natural based, fatty acid ester, designed primarily as a lubricity additive for aluminum.

S&S TMP-C18

TMP-C18 is a high quality oleic ester that exhibits excellent temperature stability and lubricity. It is a natural ISO 46 grade ester.

S&S TMP/TM

Trimethylolpropane Trimonomerate is a heat stable, low pour point synthetic polyol ester.

SMO - Sorbitan Monooleate

SMO is an ester that co-emulsifies, thickens and is used for dropping HLB. Available in both tallow and vegetable grades.

Methyl-Esters

We have a variety of methyl-esters including soy, vegetable, canola, and blends.

S&S SMR1

Drop in replacement for SMO.

OLEOTALL C21

Oleotall C21 is a series of products that are 100% active and differentiated by isomer level and acid value. This chemistry is a good coupling agent and corrosion inhibitor.

Product	Diacid Isomers	Acid Value (mgKOH/g)
Oleotall C21-DA	68% - 73%	265 - 280
Oleotall C21-LA	78% - 90%	265 - 280
Oleotall C21-HA	70% - 85%	273 - 287
Oleotall C21-DAH	> 90%	> 280

CORROSION INHIBITORS

S&S CP-B-4M

S&S CP-B-4M is a water-soluble boron containing compound for use as a corrosion inhibitor in aqueous systems. S&S CP-B-4M is diethanolamine free, yet provides a high amount of reserve alkalinity for good corrosion protection.

S&S CP-9

S&S CP-9 is a synthetic corrosion inhibitor based on a neutralized amino carboxylate used in MWF, cleaners and water glycol fluids. Effective for use on cast iron and steel alloys. Excellent hard water stability and can act to reduce foam.

S&S 199

S&S 199 is a water soluble corrosion inhibitor that can be used in various water based systems and coolants.

S&S 7056

S&S 7056 inhibits corrosion and is effective on steel surfaces both polished and ground. Specifically designed for acid atmospheres, it dissolves in aliphatic solvents and oils.

S&S 7100

S&S 7100 is a thin-film, water displacing rust preventative that provides excellent protection for salt and humid atmospheres. Also provides excellent water separating and displacing properties, while being non-staining on a variety of ferrous and non-ferrous metals.

S&S CS 42

S&S CS 42 is a high molecular weight neutral calcium sulfonate used to improve rust prevention and demulsibility in various oil based products.

S&S 6945

S&S 6945 is a high molecular weight neutral calcium sulfonate used to improve rust prevention and demulsibility in various oil based products.

S&S CS 57

S&S CS 57 is a high molecular weight slightly over-based calcium sulfonate used to improve rust prevention and demulsibility in various oil based products.

S&S CS 400

CA-400 is an oil-soluble, highly over-based calcium sulfonate with excellent corriosion protection in mill oils, short term rust preventatives, coatings and greases. Acts as an excellent demulsifier with high alkalinity and is a detergent and dispersant in lubricating oils.

S&S 7165

S&S 7165 is a thin film calcium sulfonate and a superior water displacing rust preventative in both salt and humid atmospheres when diluted in petroleum solvent or oil.

S&S 5670/5655

S&S 7165 is a thin film calcium sulfonate and a superior water displacing rust preventative in both salt and humid atmospheres when diluted in petroleum solvent or oil.

•	
•	
•	
•	
•	
•	•
•	•
	•

Solvent





BIOCIDES

PROMEX™ 20S

Promex 20S is a glycol solution of 20% 1,2-Benzisothiazolin-3-one. Used as a preservative in aqueous and water miscible chemicals, has a broad efficacy against bacteria, yeast and fungi. Excellent compatibility and long term stability for most metal working fluids.

PROMEX™ IPBC30S

Promex IPBC30S is 30% solution of 3-iodo-2-propynylbutylcarbamate and an effective fungicide for a wide range of industrial applications. Has a good safety profile and is effective over a pH range of 4-9.

CONDITIONERS

Durablend RP-T

Durablend RP-T is a cost effective pH-Buffer, rust & corrosion inhibitor, and lubricity additive.

Pel-Ron 822

Pel-Ron 822 is a unique copper complex that works to lower the required amount of biocidal agents required to stabilize diluted metal working fluids in use. Thus it helps to reduce the usual dose of biocide required. Can be added tank side or to a coolant formulation providing long term odor control.

SPECIALTY AMINES

Pel-Ine 618

Pel-Ine 618 is a tertiary amine that adds alkalinity to metal working formulations and is useful as a catalyst for both epoxy and urethane systems.

DCHA

Dicyclohexamine is a rust & corrosion inhibitor that is also a lubricity additive. Additionally, DCHA functions as a cost-effective pH buffer.

DGA

Diglycolamine is excellent in providing pH control and buffering, additionally it is non-leaching to cobalt and aluminum.

S&S 2M-Amine

S&S 2M Amine is a user friendly replacement for DCHA. It will not cause dermatitis and is more water soluble.



EMULSIFIERS

S&S TriStar Emulsifier

S&S TriStar is a polymeric based emulsifier unlike anything in the industry. This product is 100% active (no oil or diluents) and is easy to handle at ambient temperature. With little addition it will emulsify naphthenic, paraffinic, and vegetable based oils. It is compatible with phosphate esters, chlorinated paraffins, sulfurized fats, olefins and borate esters.

S&S LF-Amide

S&S LF Amide is a *low foaming*, DEA-free fatty acid alkanolamide used as a lubricant, corrosion inhibitor, and emulsifier.

S&S ALK E-70

S&S ALK-E70 is a low foam emulsifier for both mineral and vegetable oils. It is compatible with nonionic and anionic additives to formulate high performance metalworking coolants with low foam in both soft and hard water.

S&S RCO 70

S&S RCO 70 is a unique DEA-free amide that is used as a secondary emulsifier.

S&S DTT Amide

S&S DTT Amide is an excellent co-emulsifier providing excellent oxidative stability, good boundary lubrication, high reserve alkalinity and excellent corrosion protection for soluble oils, semi-synthetics, synthetics, and rust preventives.

ODG-1.0

PEL-AMID™ ODG-1.0 is a DEA-free, naturally derived 1:1 tall oil alkanolamide, which is designed for use in industrial preparations as a lubricant and emulsifier.

S&S PBase-H

PBase-H is a low cost, high molecular weight emulsifier. It's bio-stable and low-foaming properties make it an excellent replacement for both natural and synthetic sulfonates.

S&S PBase-M

S&S PBase-M is a low cost, medium molecular weight emulsifier. Along with being bio-stable and low-foaming, it is also hard water stable.

S&S PBase-L

S&S PBase-L is our lowest molecular weight in the series. Often used independently or with the PBase-M to enhance emulsification properties.

DEFOAMERS

Surtech® KE-131

Surtech® KE-131 is a modified-silicone emulsion for use as a tankside defoamer

Surtech® KE-802

Surtech® KE-802 is a low cost modified silicone emulsion used as a tankside defoamer.

Surtech® CA-3875

Surtech® CA-3875 is a modified silicone emulsion.

Surtech® HA-4760

Surtech® HA-4760 is a modified silicone emulsion.

Surtech® HA-4676

Surtech® HA-4676 is a non-silicone solution and an Ideal tankside defoamer.

Surtech® HA-1727

Surtech® HA-1727 is a non-silicone defoamer for metal working fluids and alkaline cleaners.

Surtech® OA-3321

Surtech® OA-3321 was developed as a silicone multi-functional, high efficiency foam control agent for OII-based, releasing entrained air and foam control in diesel fuel.

Surtech® OA-7885

The Surtech® OA series is designed to release, entrained air in gear oils, metal cutting oils, hydraulic oils, motor oils, compressor oils and other non-acqueous lubricants.

ANTI-OXIDANTS

RIANOX® L57

RIANOX® L57 is a liquid aromatic amine antioxidant, used for lubricating oil and grease.

RIANOX® L67

RIANOX® L67 is a nonylated diphenylamine for use as an antioxidant for lubricant applications.

RIANOX® L115

RIANOX® L115 is a high molecular weight hindered phenolic antioxidant containing sulfur.

RIANOX® 1135

RIANOX® 1135 is an active, liquid hindered phenolic antioxidant for polyols, polyurethanes, and mineral or synthetic lubricants.

RIANOX® BHT

BHT can be applied in polyolefins, such as polyethylene, polypropylene, polybutene and olefin copolymers such as EVA copolymers

MISCELLANEOUS

MR-109/London Rosin Oil

Premium rosin oil for improved lubricity and performance.

MR-849/Kidney Rosin Oil

Isononanoic Acid

An organic acid in the family of carboxylic acids. Provides lubricity, corrosion inhibition and stability to formulations. Can replace neodecanoic and caprylic acids.

TOFA/DTO

Various grades of tall oil and distilled tall oils.

Lard Oils

Various grades including prime burning, EWS, #1 lard oil.

S&S SHR 4020

Water soluble polyalkylene glycol basefluids with an ISO 20 viscosity grade.

S&S PAG-100

S&S PAG 100 is a high viscosity polyalkylene glycol base fluid which is a water soluble co-polymer. It is frequently used as a lubricant base, either where a solution in water is desirable or where water absorption may be desirable.


Pel-Pag WS-660

WS-660 is a water-soluble polyalkylene glycol with approximate viscosity of 660 SUS at 40°C.

Pel-Pag WS-5100

WS-5100 is a lubricant for metal working fludis with approximate viscosity of 5100 SUS at 40°C.





CHEMICALS FOR INDUSTRY



(631) 261-5920

www.SandSChemical.com
Support@SandSChemical.com
1000 Ft. Salonga Road, Northport NY
V 1.72